International
IOR Rectifier

IRFY044,IRFY044M
60V, N-CHANNEL
HEXFET® MOSFET TECHNOLOGY

POWER MOSFET THRU-HOLE (TO-257AA)

Product Summary

Part Number	$R_{DS(on)}$	I_D	Eyelets
IRFY044	0.040 Ω	16*A	Glass
IRFY044M	0.040 Ω	16*A	Glass

HEXFET® MOSFET technology is the key to International Rectifier's advanced line of power MOSFET transistors. The efficient geometry design achieves very low on-state resistance combined with high transconductance. HEXFET transistors also feature all of the well-established advantages of MOSFETs, such as voltage control, very fast switching, ease of paralleling and electrical parameter temperature stability. They are well-suited for applications such as switching power supplies, motor controls, inverters, choppers, audio amplifiers, high energy pulse circuits, and virtually any application where high reliability is required. The HEXFET transistor's totally isolated package eliminates the need for additional isolating material between the device and the heatsink. This improves thermal efficiency and reduces drain capacitance.



TO-257AA

Features:

- Simple Drive Requirements
- Ease of Paralleling
- Hermetically Sealed
- Electrically Isolated
- Glass Eyelets
- For Space Level Applications Refer to Ceramic Version Part Numbers IRFY044C, IRFY044CM

Absolute Maximum Ratings

	Parameter		Units
I_D @ V_{GS} = 10V, T_C = 25°C	Continuous Drain Current	16*	A
I_D @ V_{GS} = 10V, T_C = 100°C	Continuous Drain Current	16*	
I_{DM}	Pulsed Drain Current ①	156	
P_D @ T_C = 25°C	Max. Power Dissipation	100	W
	Linear Derating Factor	0.8	W/°C
V_{GS}	Gate-to-Source Voltage	±20	V
E_{AS}	Single Pulse Avalanche Energy ②	100	mJ
I_{AR}	Avalanche Current ①	16*	A
E_{AR}	Repetitive Avalanche Energy ①	10	mJ
dv/dt	Peak Diode Recovery dv/dt ③	4.5	V/ns
T_J T_{STG}	Operating Junction Storage Temperature Range	-55 to 150	°C
	Lead Temperature	300(0.063in./1.6mm from case for 10 sec)	
	Weight	3.3 (Typical)	g

* Current is limited by pin diameter
For footnotes refer to the last page

4/18/01

Electrical Characteristics @ Tj = 25°C (Unless Otherwise Specified)

	Parameter	Min	Typ	Max	Units	Test Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	60	—	—	V	V_{GS} = 0V, I_D = 1.0mA
$\Delta BV_{DSS}/\Delta T_J$	Temperature Coefficient of Breakdown Voltage	—	0.68	—	V/°C	Reference to 25°C, I_D = 1.0mA
$R_{DS(on)}$	Static Drain-to-Source On-State Resistance	—	—	0.04	Ω	V_{GS} = 10V, I_D = 16A ④
$V_{GS(th)}$	Gate Threshold Voltage	2.0	—	4.0	V	V_{DS} = V_{GS}, I_D = 250µA
g_{fs}	Forward Transconductance	17	—	—	S (℧)	V_{DS} > 15V, I_{DS} = 16A ④
I_{DSS}	Zero Gate Voltage Drain Current	—	—	25	µA	V_{DS}= 48V ,V_{GS}=0V
		—	—	250		V_{DS} = 48V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Leakage Forward	—	—	100	nA	V_{GS} = 20V
I_{GSS}	Gate-to-Source Leakage Reverse	—	—	-100		V_{GS} = -20V
Q_g	Total Gate Charge	—	—	88	nC	V_{GS} =10V, I_D = 16A
Q_{gs}	Gate-to-Source Charge	—	—	15		V_{DS} = 30V
Q_{gd}	Gate-to-Drain ('Miller') Charge	—	—	52		
$t_{d(on)}$	Turn-On Delay Time	—	—	23	ns	V_{DD} = 30V, I_D = 16A, R_G = 9.1Ω
t_r	Rise Time	—	—	130		
$t_{d(off)}$	Turn-Off Delay Time	—	—	81		
t_f	Fall Time	—	—	79		
$L_S + L_D$	Total Inductance	—	6.8	—	nH	Measured from drain lead (6mm/0.25in. from package) to source lead (6mm/0.25in. from package)
C_{iss}	Input Capacitance	—	2400	—	pF	V_{GS} = 0V, V_{DS} = 25V f = 1.0MHz
C_{oss}	Output Capacitance	—	1100	—		
C_{rss}	Reverse Transfer Capacitance	—	230	—		

Source-Drain Diode Ratings and Characteristics

	Parameter	Min	Typ	Max	Units	Test Conditions
I_S	Continuous Source Current (Body Diode)	—	—	16*	A	
I_{SM}	Pulse Source Current (Body Diode) ①	—	—	156		
V_{SD}	Diode Forward Voltage	—	—	2.5	V	T_j = 25°C, I_S = 16A, V_{GS} = 0V ④
t_{rr}	Reverse Recovery Time	—	—	220	nS	T_j = 25°C, I_F = 16A, di/dt ≤ 100A/µs
Q_{RR}	Reverse Recovery Charge	—	—	1.6	µC	V_{DD} ≤ 50V ④
t_{on}	Forward Turn-On Time	Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by $L_S + L_D$.				

* Current is limited by pin diameter

Thermal Resistance

	Parameter	Min	Typ	Max	Units	Test Conditions
R_{thJC}	Junction-to-Case	—	—	1.25	°C/W	
R_{thCS}	Case-to-sink	—	0.21	—		
R_{thJA}	Junction-to-Ambient	—	—	80		Typical socket mount

Note: Corresponding Spice and Saber models are available on the G&S Website.

For footnotes refer to the last page



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. Typical Transfer Characteristics



Fig 4. Normalized On-Resistance Vs. Temperature



Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage



13a

Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage



Fig 7. Typical Source-Drain Diode Forward Voltage



Fig 8. Maximum Safe Operating Area



Fig 9. Maximum Drain Current Vs. Case Temperature



Fig 10a. Switching Time Test Circuit



Fig 10b. Switching Time Waveforms



Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case



Fig 12a. Unclamped Inductive Test Circuit



Fig 12c. Maximum Avalanche Energy Vs. Drain Current



Fig 12b. Unclamped Inductive Waveforms



Fig 13a. Basic Gate Charge Waveform



Fig 13b. Gate Charge Test Circuit

Foot Notes:

① Repetitive Rating; Pulse width limited by maximum junction temperature.

② V_{DD} = 25V, starting T_J = 25°C, L= 0.78mH Peak I_L = 16A, V_{GS} = 10V

③ $I_{SD} \leq$ 16A, di/dt $\leq$ 100A/µs, $V_{DD} \leq$ 60V, $T_J \leq$ 150°C

④ Pulse width $\leq$ 300 µs; Duty Cycle $\leq$ 2%

Case Outline and Dimensions — TO-257AA



NOTES:

1. DIMENSIONING & TOLERANCING PER ANSI Y14.5M-1994.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
4. OUTLINE CONFORMS TO JEDEC OUTLINE TO-257AA.

LEGEND

D - DRAIN
S - SOURCE
G - GATE



International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.

Data and specifications subject to change without notice. 04/01